

Accessoires sanitaires

JOINTS / COFFRET




P25

Joint fibre ep.1,5mm

Dimension	Réf. fibre	
1/4	P2514	100
3/8	P2538	100
1/2	P2512	100
5/8	P2558	100
3/4	P2534	100
7/8	P2578	100
1"	P251	100
1"1/4	P25114	100
1"1/2	P25112	50
2"	P252	25

Application eau sanitaire
<70°C / Pression 10 bars



P26

Joint SBR 70 shore ep.2mm

Dimension	Réf. caoutchouc	
1/4	P2614	100
3/8	P2638	100
1/2	P2612	100
5/8	P2658	100
3/4	P2634	100
7/8	P2678	100
1"	P261	100
1"1/4	P26114	100
1"1/2	P26112	50
2"	P262	25

Application eau sanitaire
<70°C / T° mini: -10°C / Pression 10 bars




P27

Joint EPDM 70 shore ACS ep.2mm

Dimension	Réf. caoutchouc	
1/4	P2714	100
3/8	P2738	100
1/2	P2712	100
5/8	P2758	100
3/4	P2734	100
7/8	P2778	100
1"	P271	100
1"1/4	P27114	100
1"1/2	P27112	50
2"	P272	25

Application eau sanitaire + génie climatique
<110°C / To mini: -20°/
Pression 10 bars. Matière ACS



P28

Joint BA202 ep.2mm

Dimension	Réf. BA202	
1/4	P2814	100
3/8	P2838	100
1/2	P2812	100
5/8	P2858	100
3/4	P2834	100
7/8	P2878	100
1"	P281	100
1"1/4	P28114	100
1"1/2	P28112	50
2"	P282	25

Application eau, huiles, basses pressions /
T° mini: -20°C -150°C/+140°C
/ Pression 40 bars



P29

Joint BAU ep.2mm

Dimension	Réf. BAU	
1/4	P2914	100
3/8	P2938	100
1/2	P2912	100
5/8	P2958	100
3/4	P2934	100
7/8	P2978	100
1"	P291	100
1"1/4	P29114	100
1"1/2	P29112	50
2"	P292	25

Eau, hydrocarbures, vapeur, industrie
alimentaire / T°: -196°C/+250°C /
Pression 100 bars



P30

Joint téflon ep.1,5mm

Dimension	Réf. PTFE	
3/8	P3038	100
1/2	P3012	100
3/4	P3034	100
1"	P301	100
1"1/4	P30114	100
1"1/2	P30112	50
2"	P302	25

Application tous fluides / T° -200/+260°C

P31

Coffret 720 joints fibre

Dimension	Réf. fibre	
3/8 - 1/2 - 5/8 - 3/4 - 1" - 1"1/4 - 1"1/2	P31	720



COMPOSITION

720 Joints fibre	
Dimension	Quantité
3/8	120
1/2	300
5/8	60
3/4	90
1"	30
1"1/4	80
1"1/2	40

Tout joint démonté doit être remplacé impérativement.

Autres dimensions sur demande

Bonnel Décolletage - Catalogue général